## Problem Set #1 UBC | EECE 494 | Spring 2011

## February 22, 2011 **Due: March 4, 2011**

This problem set is an individual assignment. You are allowed to consult lecture notes, textbooks and other such material. You may discuss the questions with other persons, particularly the instructor and the teaching assistant, however all the work that you hand in must be your own. If you benefited from discussions with other persons, you must mention that person's name. If you used resources other than the lecture notes and the readings on the course website, indicate the source of the material. **Plagiarism will be dealt with severely**.

It is recommended that you add a cover page to your solutions that clearly indicates your name, your student number, and the sources that you consulted and the names of other persons with whom you discussed the problem set.

You can get a maximum of 50 marks on this problem set, which is worth 5% of the total course grade.

- 1. Indicate if the following statements are *true* or *false*. [1 point each]
  - (a) POSIX implements several scheduling policies.
  - (b) It is possible to model strictly non-preemptive execution as blocking time in a preemptive scheduling context.
  - (c) Unbounded blocking and deadlocks can be avoided by using the priority inheritance protocol.
  - (d) Aperiodic task servers help aperiodic tasks meet deadlines.
  - (e) POSIX signals are primitives that permit condition synchronization.
- 2. Consider the following task set:

Task	e <sub>i</sub>	$D_i$	$P_i$
$T_1$	2	5	6
<i>T</i> <sub>2</sub>	2	4	8
<i>T</i> <sub>3</sub>	4	8	12

- (a) What is the worst-case response time for task *T*<sub>3</sub>? [3 points]
- (b) If this task set were scheduled using the earliest deadline first policy then indicate the smallest set of time instants at which one would need to test the processor demand criterion before we can conclude that the task set is schedulable using EDF? [3 points]
- 3. Use response time analysis to verify if the following task set (with known blocking times) is schedulable using the rate monotonic scheduling policy. (One blocking term is not specified. What should it be?) [3 points]

Task	e <sub>i</sub>	$P_i$	$B_i$
$T_1$	4	10	5
$T_2$	3	15	3
<i>T</i> <sub>3</sub>	4	20	?

4. Prove the following proposition for a set of periodic tasks: For a task  $\tau_i$ , with period  $P_i$ , execution time  $e_i$ , relative deadline  $D_i$ , when all tasks are scheduled using deadline monotonic priorities, define  $S_i = \{s_{i,k}\}$  to be as follows

$$S'_{i} := \{ lP_{j} | j = 1, 2, \dots, i; l = 1, \dots, \lfloor \frac{P_{i}}{P_{j}} \rfloor \},$$
  
$$S_{i} := \{ S'_{i} - \{ t | t \in S'_{i}, t > D_{i} \} \} \cup \{ D_{i} \}.$$

(By the critical instant theorem, there is no loss of generality in assuming that all tasks release a job at time 0.)

Assume  $S_i$  is sorted in ascending order, and that j < i implies  $\tau_j$  has greater priority than  $\tau_i$ .  $\tau_i$  can meet its deadlines if there exist <u>one or more</u> time points  $s_{i,k} \in S_i$  that satisfy

$$\sum_{j=1}^{i} e_j \lceil \frac{s_{i,k}}{P_j} \rceil \leq s_{i,k}.$$

## [12 points]

- 5. In a periodic task system with relative deadlines equal to the periods, rate monotonic scheduling may do as well as the earliest deadline first policy if there is a specifici relationship among the task periods. If there are *n* tasks to be scheduled and the periods of the tasks are  $P, kP, k^2P, \ldots, k^{n-1}P$  respectively (where *k* is an integer greater than 1) then the utilization bound is 1 and not  $n(2^{1/n} 1)$ . For example, if there are four tasks and their periods are 4,8,16,32 respectively then the utilization bound is 1. In fact, when a set of tasks have periods that follow this pattern (called a *harmonic sequence*) then that set of tasks can be replaced by one virtual task for the purpose of analysis. Using this idea, develop a procedure for testing schedulability using utilization bounds giving some attention to the possibility of a harmonic chain existing. Provide a general method **[8 points]** and then use it to test the schedulability of the following task sets **[2 points each]**:
  - (a)  $(e_1 = 1.5, P_1 = 6), (2, 12), (2, 18), (1, 24), (4, 48), (6, 54), (4, 96).$
  - (b)  $(e_1 = 1, P_1 = 5), (1, 10), (1, 15), (2, 20), (1, 25), (3, 30), (2, 40), (5, 75), (2, 80), (5, 225).$
- 6. Determine if the following task set can be scheduled using the rate monotonic scheduling policy with the priority ceiling protocol to control resource access.

Task	$e_i$	$P_i$	Resources used
$T_1$	4	10	$R_1, R_2$
$T_2$	5	20	$R_2, R_3$
$T_3$	10	35	$R_3$
$T_4$	2	40	$R_1$

The duration for which each resource is used by the tasks is specified in the following table. You may assume that a task locks only one resource at a time.

Resource	Duration
$R_1$	2
$R_2$	1
$R_3$	2

7. [4 points each] You should consult the readings to answer these questions fully.

- (a) Stankovic, in his article on misconceptions about real-time computing, talks about the serializability of databases. What is serializability? Explain with an example.
- (b) How does EDF behave when the system is in a state of permanent overload (utilization > 1)? Which tasks miss deadlines? Compare this situation with the behaviour of RM scheduling under conditions of permanent overload.
- (c) How can lock-free synchronization schemes help in a real-time system? Provide a brief discussion that includes schedulability analysis issues.